

Challenges of Testing in the Unbundled Loop Environment

Cooperation for Deployment of DSL
Services

Analysts estimate 1.5 million businesses will switch from dial-up or ISDN access to DSL by 2002.

... backlog of 15,000 to 20,000 customers waiting for service.

... now that I have it, I'm never giving it up!"

"And once you get used to DSL, going back to a 56k modem would be like trading my car in for a horse and carriage!"

... But there are problems

HARRIS

DSL deployments hitting snags

By John Rendleman, *PC Week* (<http://www.zdnet.com>)

"My DSL took **9 weeks** to get installed."

"It's been nearly **13 weeks** since I have applied for DSL service in Vancouver."

"Over **2 months** now, and they're incredibly unsure if my house can get it or not. Total pain."

"... they took **9 weeks** and never hooked me up. They put the blame on everyone else."

"We didn't have trouble getting it provisioned, but we have had problems with the **reliability of our DSL**"



"... continually **adds to its work force** (now at 1,300 employees) to keep up with demand, "but that's more of an industry wide challenge than one that's individual to us,"

- New technology requires new tools and processes
- Need to help reduce the troublesome and long installation process
- Three major issues to cover
 - Remote loop access
 - Expanded physical layer testing
 - ILEC / CLEC process improvement tools

Remote Access to the Loop

HARRIS


- Many DSLAMs don't have test access built-in
- For those DSLAMs that don't...
- Need separate Loop Access product
- Harris' Carrier Test Access Switch (CTAS)
 - Installed between DSLAM and MDF
 - Supports up to 128 pair
 - Daisy chained to scale easily



Remote Access to the Loop

HARRIS

- But many DSLAMs do have test access built-in
- For those it's best to have a direct interface to the test equipment
- Similar to most switches and DLCs




Expanded Loop Testing

HARRIS

- DSL still relies on the local loop, so much of the physical layer testing is applicable and necessary
 - Accurate three terminal testing
 - AC/DC opens, shorts, grounds
 - Capacitive measurement
 - Length
 - Balance
 - Noise tests:
 - Longitudinal balance
 - Metallic
 - C-message
 - Load coil detection and spacing
 - Interactive tests with the field technician


**Measurement Accuracy
2-Terminal Vs. 3-Terminal Test**



| CRAFT: DC SIGNATURE | | | |
|---------------------|--------------|--|-----|
| <u>KOHMS</u> | <u>VOLTS</u> | | |
| 100.0 | | | T-R |
| 75.0 | 0.00 | | T-G |
| 75.0 | 0.00 | | R-G |

| RTU: DC SIGNATURE | | | |
|-------------------|--------------|--|-----|
| <u>KOHMS</u> | <u>VOLTS</u> | | |
| 200.0 | | | T-R |
| 100.0 | 0.00 | | T-G |
| 100.0 | 0.00 | | R-G |


- DSL needs more...
- High frequency noise testing
 - Used to more accurately pre-qualify lines, finding high frequency noise that the RTU alone can't measure
 - Also used to help troubleshoot and recognize crosstalk noise



Bridged Tap Detection

HARRIS


- Bridged tap detection and location
 - Determines the presence of bridged taps using single-ended testing
 - Saves dispatch time by not requiring double-ended testing
- Bridged taps cause trouble for DSL
 - Relatively long taps that are close to the end of the copper pair are especially troublesome.



ILEC / CLEC Process


HARRIS

- CLEC / ILEC interactions still not too automated
- Inefficient operations - too many dispatches required
- A sample of the “old” process...





- Interactive Voice Access

- Allows remote voice (touch-tone) access to the test system
- Deployed by the CLEC - but can be used by either the ILEC or CLEC technicians
- Vastly improves CLEC efficiency by minimizing the number of people needed at the operations center
- ILECs more efficient since they have access to the loop
 - Tone on the line to help find the pair
 - Testing for troubleshooting during install




- Electronic Test Tag

- Proves Circuit Continuity to Minimum Point Of Entry (MPOE)
- Better than a Half-Ringer
 - No False Ringer Termination
 - Full Multimeter Testing of Loop in Inactive State
 - Positive Signature When Activated
- Reusable on Subsequent Installations
- Compatible with Current Harris RTU Hardware and Software



Old vs. New Process

HARRIS



- Harris offers a variety of products offered to CLECs and ILECs:
 - Comprehensive Line Testing
 - Remote Loop Access
 - IVA for field access to the system
 - ETT for positive line signature
- Helping to address the obstacles to fast and efficient DSL deployment, troubleshooting and maintenance



Thank you!

Questions?